

Specification of Segregation Machine

SNo.	Item Description	Quantity	Power HP	Total Amount																										
1.	<p>Crusher</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">Body</td> <td>MS fabricated 10mm thick</td> </tr> <tr> <td>Shaft</td> <td>1 No. EN-8</td> </tr> <tr> <td>Beaters</td> <td>EN-9</td> </tr> <tr> <td>Motor</td> <td>5HP</td> </tr> <tr> <td>Drive</td> <td>V belt, C grooves, 2 section</td> </tr> <tr> <td>Inlet and outlet chute</td> <td>1 set</td> </tr> <tr> <td>Electric Starter</td> <td>DOL type</td> </tr> </table>	Body	MS fabricated 10mm thick	Shaft	1 No. EN-8	Beaters	EN-9	Motor	5HP	Drive	V belt, C grooves, 2 section	Inlet and outlet chute	1 set	Electric Starter	DOL type	1	10HP													
Body	MS fabricated 10mm thick																													
Shaft	1 No. EN-8																													
Beaters	EN-9																													
Motor	5HP																													
Drive	V belt, C grooves, 2 section																													
Inlet and outlet chute	1 set																													
Electric Starter	DOL type																													
2.	<p>Trommel (For Segregation of Waste)</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">Drum</td> <td>Fabricated From MS 2062 sheet</td> </tr> <tr> <td>Dimension</td> <td>1600mm Dia 5000mm Length</td> </tr> <tr> <td>Capacity</td> <td>60 TPD</td> </tr> <tr> <td>Screen</td> <td>50mm holes perforated MS Sheet</td> </tr> <tr> <td>Support Rollers</td> <td>4 no., each on ends</td> </tr> <tr> <td>RPM</td> <td>12-18 RPM</td> </tr> <tr> <td>Cover Plate</td> <td>2 thick MS plate</td> </tr> <tr> <td>Motor</td> <td>5HP, Crompton Greaves</td> </tr> <tr> <td>Gear Box 5HP</td> <td>U-400, Ratio 1:30 Classic make</td> </tr> <tr> <td>Structure</td> <td>Heavy ISMC 100MS frame</td> </tr> <tr> <td>Bearing</td> <td>UCP Type</td> </tr> <tr> <td>Shaft</td> <td>En-8</td> </tr> <tr> <td>Electric Starter</td> <td>Dol Switch</td> </tr> </table>	Drum	Fabricated From MS 2062 sheet	Dimension	1600mm Dia 5000mm Length	Capacity	60 TPD	Screen	50mm holes perforated MS Sheet	Support Rollers	4 no., each on ends	RPM	12-18 RPM	Cover Plate	2 thick MS plate	Motor	5HP, Crompton Greaves	Gear Box 5HP	U-400, Ratio 1:30 Classic make	Structure	Heavy ISMC 100MS frame	Bearing	UCP Type	Shaft	En-8	Electric Starter	Dol Switch	1	10HP	
Drum	Fabricated From MS 2062 sheet																													
Dimension	1600mm Dia 5000mm Length																													
Capacity	60 TPD																													
Screen	50mm holes perforated MS Sheet																													
Support Rollers	4 no., each on ends																													
RPM	12-18 RPM																													
Cover Plate	2 thick MS plate																													
Motor	5HP, Crompton Greaves																													
Gear Box 5HP	U-400, Ratio 1:30 Classic make																													
Structure	Heavy ISMC 100MS frame																													
Bearing	UCP Type																													
Shaft	En-8																													
Electric Starter	Dol Switch																													
3.	Waste Feed belt with Feed Hooper	1	6HP																											

	Grade	M-24			
	Width	800mmendless			
	Length	10Meters			
	Ply	3 ply Nylon			
	Top duck	3mm			
	Bottom duck	1.5mm			
	Frame	MS channel			
	Head drum pulley	Dia.220mm			
	Tail drum pulley	Dia.220mm			
	Motor	3HP			
	Gearbox	30:1			
	Coupling	Tyre coupling			
	Drive Sprocket	5/8"Pitch,MS fabricated			
	Driven Sprocket	5/8"Pitch,MS fabricated			
	Drive chain	5/8"Pitch			
	Electric Starter	DOL type			
	Feed Hooper	4 mm Ms Plate			
4.	Sorting belt 1&2		1	10HP	
	Grade	M-24			
	Width	800mmendless			
	Length	12Meters			
	Ply	3 ply Nylon			
	Top duck	3mm			
	Bottom duck	1.5mm			
	Frame	MS channel			
	Head drum pulley	Dia.220mm			
	Tail drum pulley	Dia.220mm			
	Motor	5HP			
	Gearbox	30:1			
	Coupling	Tyre coupling			
	Drive Sprocket	5/8"Pitch, MS fabricated			
	Driven Sprocket	5/8"Pitch,MS fabricated			
	Drive chain	5/8"Pitch			
	Electric Starter	DOL type			
	Side Walls	100mm Height			
5.	Final Product Sorting belt(upper& Lower)		1	15HP	

	Grade	M-24		
	Width	800 mm endless		
	Length	18Meters		
	Ply	3 ply Nylon		
	Top duck	3mm		
	Bottom duck	1.5mm		
	Frame	MS channel		
	Head drum pulley	Dia.220mm		
	Tail drum pulley	Dia.220mm		
	Motor	7.5HP		
	Gearbox	30:1		
	Coupling	Tyre coupling		
	Drive Sprocket	5/8"Pitch,MS fabricated		
	Driven Sprocket	5/8"Pitch, MS fabricated		
	Drive chain	5/8"Pitch		
	Electric Starter	DOL type		
	Side Walls	100mm Height		
6.	Bailer Machine		1	10HP
	Body	MS fabricated		
	Motor	5HP		
TOTAL				

Warranty

1. All supplies shall be in conformity with the specifications mentioned in the quotation.
2. All the equipment and machinery under condition of normal operation shall show no defect due to faulty design, material and/or workmanship.
3. All the equipment shall perform satisfactorily to produce Product

1. The Warrantee is for a period of 12 months

We shall not be responsible for the following which are excluded from the warrantee:
Normal wear & tear of parts on which repair, alteration or adjustments have been performed or begun by owner or third parties without our previous consent expecting in the normal maintenance