

"Industrial, Touristic and Green City, Clean, Safe and Prosperous City"



**Damak Municipality**  
**Office of the Municipal Executive**  
**Damak, Jhapa**  
**Koshi Province, Nepal**



**Technical Compliance Sheet for 4 MP ANPR Camera**

<b>Feature</b>	<b>Specification</b>	<b>Compliance (Fully Compliant, Partially Compliant, Non Compliant) or Bidders Offer</b>
<b>Manufacture</b>		
<b>Brand</b>		
<b>Model No</b>		
<b>Camera</b>		
Image Sensor	1/1.8" Progressive Scan CMOS	
Max. Resolution	2688 × 1520	
Min. Illumination	Color: 0.0005 Lux @ (F1.2, AGC ON), 0 Lux with light	
Shutter Speed	1/25 s to 1/100,000 s	
Day & Night	24/7 color imaging	
<b>Lens</b>		
Type	Fixed Focal Length, 2.8mm, 4mm	
Lens Type & FOV	2.8-12mm : Horizontal: 113.5° to 39°, Vertical: 58.4° to 22.7°, Diagonal: 141.3° to 44.3° 8-32mm : Horizontal: 41.9° to 15.1°, Vertical: 22.9° to 8.64°, Diagonal: 48.8° to 17.3° 10-50mm: Horizontal: 32.2° to 7.8°, Vertical: 18.1° to 4.4°, Diagonal: 37.1° to 8.95°	
Focus	Auto	
Iris Type	DC-IRIS	
Aperture	2.8-12mm : F1.38, 8-32mm : F1.7, 10-50mm : F1.7	
<b>Illuminator</b>		
Built-in Supplement Light Type	White light	

Built-in Supplement Light Range	Up to 50 m	
Supplement Light Number	3	
<b>Video</b>		
Main Stream	50 Hz: 25 fps (2688 × 1520, 1920 × 1080, 1280 × 760, 704 × 576, 352 × 288) 60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 760, 704 × 576, 352 × 288)	
Sub Stream	50 Hz: 25 fps (1920 × 1080, 1280 × 760, 704 × 576, 352 × 288) 60 Hz: 30 fps (1920 × 1080, 1280 × 760, 704 × 576, 352 × 288)	
Third Stream	50 Hz: 25 fps (1280 × 760, 704 × 576, 352 × 288) 60 Hz: 30 fps (1280 × 760, 704 × 576, 352 × 288)	
Video Compression	H.264 and H.265 encoding, Main stream: H.265/H.264/MJPEG, Sub-stream: H.265/H.264/MJPEG	
Video Bit Rate	32 Kbps to 16 Mbps	
H.264 Type	Baseline Profile/Main Profile/High Profile	
H.265 Type	Main Profile	
Audio Compression	G.711/G.722.1	
Audio Bit Rate	8Kbps (G.711) /16Kbps (G.722.1)	
<b>Network</b>		
Simultaneous Live View	Up to 6 channels	
API	ISAPI,SDK,ISUP,ONVIF (PROFILE S, PROFILE G, PROFILE T, PROFILE M)	
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,SFTP, DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP, SMTP,SNMP,IGMP,802.1X,QoS,IPv4/IPv6, UDP,SSL/TLS,ISUP,ARP	
User/Host	Up to 32 users. 3 user levels: administrator, operator and user	
Security	Password protection, Complicated password, HTTPS encryption,802.1X authentication (EAP-PEAP, EAP-LEAP, EAP-MD5),Watermark, IP address filter, Basic and digest authentication for HTTP/HTTPS,WSSE	

	and digest authentication for ONVIF, RTP/RTSP over HTTPS, Control timeout settings, Security audit log, TLS 1.2, 1.3, Host authentication (MAC address)	
Network Storage	Micro SD/TF card (512 GB), local storage and CVR, NVR, ANR	
Web Browser	Supported Yes	
<b>Image</b>		
Day/Night Switch	Auto/Scheduled/Manual	
Image Enhancement	BLC, 3D DNR	
Wide Dynamic Range (WDR)	140 dB	
Image Settings	Saturation, Brightness, Contrast, Sharpness, Gain, White balance, Adjustable by client software or web browser., AGC	
<b>Interface</b>		
On-board Storage	Built-in memory card slot, supporting microSD/SDHC/SDXC card, up to 512GB	
Ethernet Interface	1 RJ45 10M/100M/1000M Ethernet interface	
Audio	Supported	
Alarm	1 input interface, 1 output interface, 2 relays	
<b>Event</b>		
Basic Event	HDD error, Network disconnected, IP address conflict	
Coverage	Up to 3 lane(s)	
Smart Function	Traffic flow detection : Average speed, traffic flow, queuing length, and traffic status Incident detection: congestion, stopped vehicle, lane change, wrong-way driving, speeding, low-speed driving	
<b>Road Traffic and Vehicle Detection</b>		
Accuracy (Under	Capture rate > 99%,	
Recommended Installation And lighting conditions	Vehicle moving direction recognition accuracy > 98.5%, LPR accuracy > 98%, Mistaken capture rate < 2%	
No License Plate Detection	Supported	
Motorcycle LPR	Supported	

Vehicle Type/ Vehicle Color	Car, Van ,Bus, Truck, Light Truck, SUV(MPV), Pickup, Motorcycle, Tricycle Red, yellow, green, blue, pink, purple, cyan, brown, white, grey, black Recognizable at daytime only	
<b>General</b>		
Power	DC 12 V to 24 V, 1.25 A, max. 15 W, two-core terminal block, PoE: 802.3at, Type 2, Class 4, max. 15 W	
Capture Speed Range	5 to 120 km/h	
Blocklist and Allow list	Max. 50000 records	
Material	Aluminum alloy	
Web Client Language	English	
General Function	One-key reset, three streams, heartbeat, password protection, watermark	
Startup and Operating Conditions	-30 °C to 70 °C (-22 °F to 158 °F). Humidity 95% or less (non-condensing) 30 °C to 70 °C (- 22 °F to 158 °F). Humidity 95% or less (non- condensing)	
<b>Approval</b>		
EMC	Yes	
Safety	Yes	
Environment	Yes	
Protection	IK10, IP67	

"Industrial, Touristic and Green City, Clean, Safe and Prosperous City"



**Damak Municipality**  
**Office of the Municipal Executive**  
**Damak, Jhapa**  
**Koshi Province, Nepal**



**Technical Compliance Sheet for 8 MP Bullet Camera**

<b>Feature</b>	<b>Specification</b>	<b>Compliance (Fully Compliant, Partially Compliant, Non Compliant) or Bidders Offer</b>
<b>Manufacture, Country</b>	To filled by Bidder	
<b>Brand Name</b>	To filled by Bidder	
<b>Model No.</b>	To filled by Bidder	
<b>Image Sensor</b>	1/1.2" Progressive Scan CMOS	
<b>Max. Resolution</b>	3840 × 2160	
<b>Min. Illumination</b>	Color: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with Light	
<b>Shutter Time</b>	1/3 s to 1/100,000 s	
<b>Day &amp; Night</b>	24/7 Color	
<b>Angle Adjustment</b>	Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°	
<b>Focal Length &amp; FOV</b>	2.8 mm: horizontal FOV 102°, vertical FOV 52°, diagonal FOV 124° 4 mm: horizontal FOV 88°, vertical FOV 47°, diagonal FOV 104° 6 mm: horizontal FOV 54°, vertical FOV 30°, diagonal FOV 62°	
<b>Aperture</b>	F1.0	
<b>Supplement Light Range</b>	White light Up to 40 m	
<b>Main Stream</b>	50 Hz: 25 fps (3840 × 2160, 3200 × 1800 , 2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 24 fps (3840 × 2160) 30 fps (3200 x 1800 , 2688 × 1520, 1920 × 1080, 1280 × 720)	
<b>Sub-Stream</b>	50 Hz: 25 fps (640 × 480, 640 × 360), 60 Hz: 30 fps (640 × 480, 640 × 360)	
<b>Third Stream</b>	50 Hz: 10 fps (1920 x 1080 , 1280 × 720, 640 × 480, 640 × 360) 60 Hz: 10 fps (1920 x 1080 , 1280 × 720, 640 × 480, 640 × 360)	
<b>Video Compression</b>	Main stream: H.265/H.264/H.264+/H.265+ Sub-stream: H.265/H.264/MJPEG Third stream: H.265/H.264	

<b>Protocols</b>	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, Web Sockets	
<b>API</b>	Open Network Video Interface (Profile S, Profile G, Profile T), ISAPI, SDK	
<b>Region Of Interest</b>	1 fixed region for main stream and sub-stream	
<b>Audio Compression</b>	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC-LC, Environment Noise Filtering-UF: Yes	
<b>Image</b>	Day, Night, Auto, Schedule, BLC, HLC, 3D DNR, Rotate, mirror, privacy mask, saturation, brightness, contrast, sharpness, gain, white balance adjustable by client software or web browser	
<b>Ethernet Interface</b>	1 RJ45 10 M/100 M self-adaptive Ethernet port	
<b>Basic Event</b>	Motion detection (human and vehicle targets classification), video tampering alarm, exception (network disconnected, IP address conflict, illegal login, HDD full, HDD error)	
<b>Power</b>	12 VDC $\pm$ 25%, 0.5 A, max. 6 W, $\varnothing$ 5.5 mm coaxial power plug, reverse polarity protection PoE: (802.3af, Class 3, 36 V to 57 V), 0.25 A to 0.15 A, max. 7.5 W	
<b>Protection</b>	IP67 (IEC 60529-2013)	

"Industrial, Touristic and Green City, Clean, Safe and Prosperous City"



**Damak Municipality**  
**Office of the Municipal Executive**  
**Damak, Jhapa**  
**Koshi Province, Nepal**



***Technical Compliance Sheet for 10 TB Hard Disk***

<b><i>Feature</i></b>	<b><i>Specification</i></b>	<b><i>Compliance (Fully Compliant, Partially Compliant, Non Compliant) or Bidders Offer</i></b>
<b><i>Manufacture</i></b>		
<b><i>Brand</i></b>		
<b><i>Model No</i></b>		
Form factor	3.5-inch (Compatible with provided NAS)	
Interface	SATA 6.0 Gbit/s	
RoHS compatible	Yes	
Halogen Free	Yes	
Rotational speed	7,200 rpm	
Buffer size	256 MB	
Transfer Rate	up to 215MB/s	
24/7 operation	Supported	
Warranty	2 years	

**Bill of Quantity (BOQ)**

To Damak Municipality,  
Office of Municipal Executive  
Damak, Jhapa  
Koshi Province, Nepal

**Subject: Rate Submission for Bus Park CCTV in Ward No. 6, FY 2081-082**

<b>SN</b>	<b>Item</b>	<b>Unit</b>	<b>Qty</b>	<b>Unit Price</b>	<b>Unit Price in Words</b>	<b>Total</b>
1	Electricity Concentric Cable 10mm	meter	500			
2	ANPR 4MP Camera with pole mount	pcs	1			
3	8 MP IP Bullet Color Camera	pcs	8			
4	10 TB Surveillance HDD (for Road Surveillance )	pcs	1			
5	Pole Mount Bracket Industry Standard	pcs	8			
6	Water proof Junction Box(ABS Material size min 290*215mm, depth 84mm)	pcs	4			
7	4 Port PoE Switch with 2 Uplink	pcs	4			
8	Outdoor PureCopper Cat6 Cable (305m)	drum	1			
9	1 DPMCB 6A	site	4			
10	Installation Charge (with All complete Work, electrical wires, tapes, RJ45etc ) All the cameras should be	ls	1			



installed in the NVR Which is located in Ward 6 Office. The network shall be provided by Municipality				
<b>Total</b>				
<b>VAT 13%</b>				
<b>Total with VAT</b>				

**Submitted By:**

**Signature:**

**Name of Designation of:**

**Signatory:**

**Firms Name:**

**Seal of the Firm:**